AlphaStation XP900
V1.0—11 June 1999
Systems and Options Catalog

Product Description

The AlphaStation XP900 is the second Compaq design center for the new generation EV6 workstation family. It is based on the Alpha 21264 microprocessor 466 MHz CPU with 2 MB ECC cache and is focused on providing a rackable, small-footprint, low-cost platform for software developers and application users. The AlphaStation XP900 is available in a Desktop configuration with either Compaq's Tru64 UNIX, OpenVMS, or LINUX-ready (operating-system less). Integrated on the system motherboard are Dual 10/100 BaseT ethernet ports, a floppy diskette controller, two serial ports, one parallel port, and keyboard and mouse interfaces. A PCI-based SCSI adapter and a SCSI cable kit are required to support internal and external SCSI disks and tape.

The AlphaStation XP900 supports five internal storage devices, including a floppy diskette, a CD-ROM, and three hard disk drive bays. Each system supports up to 1 GB of memory and 27 GB of internal storage when three 9 GB SCSI disks are installed.

The AlphaStation XP900 is the first high performance Alpha-powered EV6 workstation supporting Compaq's OpenVMS operating environment and underlines Compaq's ongoing commitment to OpenVMS customers.

Compaq's AlphaStation XP900 is available from qualified workstation sales representatives and through distribution partners. A list of eligible partners is available through local Compaq Sales Offices.

Compaq AlphaStation XP900 Workstations are available as:

- **System Building Blocks/Configure To Order Models** designed for "a la carte" ordering and distributor integration. System Building Blocks contain a system kernel, no memory, a SCSI cable, no hard disk drive, and no graphics. Additional options are factory integrated and shipped as a complete system**.**
- **Packaged Systems/ Build To Order Models** are designed for ease of ordering and stocking. Packaged Systems contain a system kernel, a minimum of 128 MB memory, Ultra-2 SCSI disk adapter, a SCSI cable, 9.1 GB hard disk drive, ELSA Gloria graphics card and PCI based audio card, and factory-installed operating systems including either Tru64 UNIX, OpenVMS, or LINUX-ready (operating-system less). Additional options will not be factory integrated into packaged systems.

Compaq AlphaStation XP900 Workstations come standard with a three-year limited warranty. Year one features on-site service; years two and three are return to Compaq service, parts only. This warranty represents one of the most comprehensive in the industry.

NOTE: AlphaStation XP900 Workstations are expected to commerce shipping in August. This SOC represents the options which are expected to be available at that time.

Compaq and the names of Compaq products referenced herein are either trademarks and/or service marks or registered trademarks and/or service marks of Compaq. DIGITAL is a Trademark of Compaq Computer Corporation.

Microsoft, Windows, Windows NT, SQL Server, Office and BackOffice are either trademarks or registered trademarks of Microsoft Corporation.

Intel and Pentium are registered trademarks of Intel Corporation.

Other product and company names mentioned herein may be trademarks and/or service marks of their respective owners.

Step 1—AlphaStation XP900 Desktop Systems

AlphaStation XP900 Desktop Systems include:

- Alpha 21264 466 MHz microprocessor with 2 MB onboard ECC cache
- Integrated dual 10/100 Base T Ethernet ports

Four PCI expansion slots (three 64-bit/one 32-bit)
- Mandatory Graphics (check table below) / 1 slot
- Mandatory SCSI Controller / 1 slot
- Two available PCI slots

- 4 DIMM memory slots (2 memory kits @ 2 DIMMs per kit) up to 1 GB maximum
- Five storage bays
  - One diskette drive bay with 1.44 MB floppy drive
  - One CD-ROM drive bay with 600 MB CD-ROM
  - One 5.25-inch x 1.6-inch removable media bay or 3.5-inch x 1-inch hard disk drive bay
  - Two 3.5-inch x 1-inch internal hard disk drive bays
- Two serial ports
  - One serial port with full duplex asynchronous modem control
  - One Remote Management Console
- One bi-directional enhanced parallel port
- 300+ W (120/240V, 60/50 Hz) power supply

Step 1a—System Building Blocks – Configure To Order

Order Number		Memory	Hard Disk Drive	Ethernet	Audio Card	Graphics Card	Operating System
SN DB10W-A4	**149819-B21**	0 MB	0	Onboard	Optional	Mandatory	OVMS
SN DB10W-A3	**149820-B21**	0 MB	0	Onboard	Not Supported	Optional	TRU64 UNIX
SN DB10W-A1	**149822-B21**	0 MB	0	Onboard	Not Supported	Optional	LINUX-ready/No OS

**Step 1b—Original OVMS VS10 models (includes SN-AVH10-AB Ensonic audio card). Replaced by SN-DB10W-A4 / 149819-B21 in Step 1a.

Order Number		Memory	Hard Disk Drive	Ethernet	Audio Card	Graphics	Monitor
SN-PB10A-AB	----	128 MB	Mandatory	Onboard	Installed	Mandatory	Optional
SN-PB10A-AC	----	256 MB	Mandatory	Onboard	Installed	Mandatory	Optional
SN-PB10A-AD	----	512 MB	Mandatory	Onboard	Installed	Mandatory	Optional

** Listed here for reference only. Step 1b models will be removed from the price list by the end of June.

Step 1c—Mandatory Options

- **Selection of a Graphics option is mandatory.**
- **Selection of a System Disk drive is mandatory. Systems support a total of three internal disk drives.**
- **Selection of a SCSI controller and Cable Kit is mandatory.**
- **9.1 GB disk drive is recommended as system disk. If more than one size of disk is ordered the operating system will be factory installed on the smallest disk.**

Step 1d—Memory Options

- **Systems include one memory kit.**
- **Systems support a maximum of two memory kits. Each kit includes two industry standard DIMMs with ECC support.**
- **Systems support maximum of 1 GB memory.**

Order Number		
SN-MS310-AA	**149834-B21**	64 MB, Two 200 pin, 100 MHz, 32 MB DIMMs
SN-MS310-BA	**149835-B21**	128 MB, Two 200 pin, 100 MHz, 64 MB DIMMs
SN-MS310-CA	**149836-B21**	256 MB, Two 200 pin, 100 MHz, 128 MB DIMMs
SN-MS310-DA	**149837-B21**	512 MB, Two 200 pin, 100 MHz, 256 MB DIMMs

Step 1—AlphaStation XP900 Desktop System *(continued)*

Step 1e—Graphics Options

- **System supports maximum of 2 graphics adapters**
- **ELSA Gloria Synergy card only supported in lower two PCI slots**

SN-PBXGK-BB	**400712-B21**	ELSA Gloria Synergy PCI video adapter
SN-PBXGB-AA	**102413-B21**	PowerStorm 3D30 graphics adapter

Step 1f—Internal Storage

SCSI Disk Drives

SN-PBXRW-SC	**146443-B21**	9.1GB Ultra2 LVD Wide SCSI 7200 RPM hard disc drive 1.0-inch bay
SN-PBXRW-TB	**146444-B21**	18.2GB Ultra2 LVD Wide SCSI 7200 RPM hard disk drive 1.0-inch bay
SN-PBXRW-RB	**388265-B21**	4.3 GB Ultra2 LVD Wide SCSI 10K RPM hard disk drive, 1.0-inch bay
SN-PBXRW-VA	**388266-B21**	9.1 GB Ultra2 LVD Wide SCSI 10K RPM hard disk drive, 1.0-inch bay

Step 1g—External Storage

SCSI Adapters

			Maximum # Supported		
Order Number		**SCSI Adapter**	**Tru64UNIX v4.0F**	**OVMS v7.1-2**	**WinNT v4.0**
SN-KZPBA-CA	**388272-B21**	PCI-based one port UltraSCSI Single-ended adapter	1	1	1
SN-KZPCA-AA	**136237-B21**	PCI-based one port Ultra-2 wide (LVD) SCSI adapter	1	1	1
SN-KZPBA-CB	**388273-B21**	PCI-based one port UltraSCSI Differential adapter (external drive only)	1	1	1

SCSI Cable Kit – Only required with Step 1b

Order Number	**SCSI Cable Kit**
3X-BN50A-01	SCSI cable kit (includes SCSI cable and SCSI LED cable)

Step 1h—Audio Option

SN-AVH10-AB	**400712-B21**	Ensonic Audio Card

Step 2—Packaged Systems

- **All packaged systems contain a system kernel with, a minimum of 128MB memory, Ultra-2 SCSI (LVD) adapter, SCSI cable, 9.1 GB 7200 RPM hard disk drive, ELSA GLoria Synergy graphics card and PCI based audio card, and factory installed operating systems, including Tru64, OpenVMS, or LINUX-ready (no operating system).**
- **Selection of country kit from step 6 is mandatory for European packages.**
- **Additional options will not be factory integrated into packaged systems and will ship seperately (as spares).**

Step 2—Packaged Systems *(continued)*

466 MHz Packaged Systems—Tru64 UNIX

Order Number		Memory / Cache	Graphics	7.2K RPM Hard Disk	Country / Keyboard
SN-DB10Q-VC	**149823-003**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	US – included
SN-DB10Q-EC	**149823-023**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	EURO – mandatory
SN-DB10Q-JC	**149823-293**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	JPN2 – included
SN-DB10Q-HC	**149823-393**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	JPN/EN – included
SN-DB10Q-CC	**149823-373**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	A/P - included

466 MHz Packaged Systems—Open VMS

Order Number		Memory / Cache	Graphics	7.2K RPM Hard Disk	Country / Keyboard
SN-DB10Q-VD	**149823-004**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	US – included
SN-DB10Q-ED	**149823-024**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	EURO – mandatory
SN-DB10Q-JD	**149823-294**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	JPN2 – included
SN-DB10Q-HD	**149823-394**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	JPN/EN – included
SN-DB10Q-CD	**149823-374**	128 MB	ELSA GLoria Synergy	9.1 GB SCSI disk	A/P - included

466 MHz Packaged Systems—LINUX-ready (No Operating System)

Order Number		Memory / Cache	Graphics	7.2K RPM Hard Disk	Country / Keyboard
SN-DB10Q-VA	**149823-001**	128 MB	Optional	9.1 GB SCSI disk	US – included
SN-DB10Q-EA	**149823-021**	128 MB	Optional	9.1 GB SCSI disk	EURO – mandatory
SN-DB10Q-JA	**149823-291**	128 MB	Optional	9.1 GB SCSI disk	JPN2 – included
SN-DB10Q-HA	**149823-391**	128 MB	Optional	9.1 GB SCSI disk	JPN/EN – included
SN-DB10Q-CA	**149823-371**	128 MB	Optional	9.1 GB SCSI disk	A/P - included

Step 3—Memory Options

- **Systems include one memory kit.**
- **Systems support a maximum of two memory kits. Each kit includes two industry standard DIMMs with ECC support.**
- **Systems support maximum of 1 GB memory.**

Order Number		
SN-MS310-AA	**149834-B21**	64 MB, Two 200 pin, 100 MHz, 32 MB DIMMs
SN-MS310-BA	**149835-B21**	128 MB, Two 200 pin, 100 MHz, 64 MB DIMMs
SN-MS310-CA	**149836-B21**	256 MB, Two 200 pin, 100 MHz, 128 MB DIMMs
SN-MS310-DA	**149837-B21**	512 MB, Two 200 pin, 100 MHz, 256 MB DIMMs

Step 4—Graphics Options

- **System supports maximum of 2 graphics adapters**
- **ELSA Gloria Synergy card only supported in lower two PCI slots**

SN-PBXGK-BB	**400712-B21**	ELSA Gloria Synergy PCI video adapter
SN-PBXGB-AA	**102413-B21**	PowerStorm 3D30 graphics adapter

Step 5—Storage

- **Packaged systems/BTO models include one 600 MB 32X CD-ROM drive, one 1.44 MB floppy drive and one 9.1GB 7200 RPM SCSI disk drive in dedicated slots.**
- **Additional internal storage supported:**
  - **Two 1” hard disk drive bays or one 1” disk plus one 1.6-inch disk.**

Step 5a—Internal Storage

SCSI Disk Drives

SN-PBXRW-RB	**388265-B21**	4.3 GB Ultra2 LVD Wide SCSI 10K RPM hard disk drive, 1.0-inch bay
SN-PBXRW-VA	**388266-B21**	9.1 GB Ultra2 LVD Wide SCSI 10K RPM hard disk drive, 1.0-inch bay
SN-PBXRW-TB	**146444-B21**	18.2 GB Ultra2 LVD Wide SCSI 10K RPM hard disk drive, 1.0-inch bay
SN-PBXRW-SC	**146443-B21**	9.1 GB Ultra2 LVD Wide SCSI 10K RPM hard disk drive, 1.0-inch bay

Removable Media Devices

TLZ10-LB	TLZ10 DAT 4 mm Internal Tape Drive (requires PBXKP-BA adapter)

Step 5b—External Storage

Tabletop DAT Tape Drives

TLZ9L-DB	32/64 GB Tabletop DAT Loader
TKZ9F-TA	5,7,10,14GB 8 mm tbitp, SE SCSI
TLZ9L-VA	32/64 GB DAT loader in Carrier

Additional SCSI Adapters

- One SN-KZPCA-AA / 136237-B21 Ultra-2 Wide (LVD) SCSI adapter included in packaged systems / BTO models)

			Maximum # Supported		
Order Number		**SCSI Adapter**	**Tru64UNIX v4.0F**	**OVMS v7.1.2**	**WinNT v4.0**
SN-KZPCA-AA	**136237-B21**	PCI-based one port Ultra-2 wide (LVD) SCSI adapter	1	1	1
SN-KZPBA-CA	**388272-B21**	PCI-based one port UltraSCSI Single-ended adapter	1	1	1
SN-KZPBA-CB	**388273-B21**	PCI-based one port UltraSCSI Differential adapter	1	1	1

Step 6—Monitors

Graphics monitors other than those listed below can be used if compatible with SVGA graphics ordered with a system.

Note: Selection of a country specific power cord is mandatory for all monitor variants.

3R-VRQV5-24/11	15” Corporate Series auto-scan color monitor, VGA to 1024 x 768 @ 75 Hz. Requires mandatory selection of country specific power cord for all variants. –24 = Northern Hemisphere without power cord –11 = Southern Hemisphere without power cord

Step 6—Monitors *(continued)*

SN-VRQP7-24/23 307806-B23/B23	17” (16.0” viewable image size) professional series auto-scanning color monitor, Trinitron CRT, 0.25 mm aperture grill pitch, VGA to 1280 x 1024 at 85 Hz, TCO 95, MPR-II, Energy Star, attached 1.8 meter video cable. Requires mandatory selection of country specific power cord for all variants. –24 = Northern Hemisphere without power cord –23 = Southern Hemisphere without power cord
SN-VRQP1-24/23 325600-B23/B23	21” (19.6” viewable image size) auto-scanning color monitor, Trinitron CRT, 0.25 mm aperture grill pitch, VGA to 1600 x 1200 at 75 Hz NI, TCO 95, Energy Star, includes a 1.8 meter video cable. Requires mandatory selection of country specific power cord for all variants. –24 = Northern Hemisphere without power cord –23 = Southern Hemisphere without power cord

SN-VRQF8-24 307906-001	TFT 8000 18” flat panel monitor . 18 inch viewable image size. TFT active matrix. In plane switching technology 160 degrees viewing angles. 1280x1024 resolution. Brightness 165 nits. Detachable base. Requires ELSA Gloria Synergy video adapter.

Step 7—Country Kits

- **Additional Windows NT languages may be purchased directly from Microsoft.**
- **Country kit is required for system to be operational.**
- **Only one country kit is allowed per system.**
- **Bulk system orders must include country kits equal to the total number of systems ordered.**
- **LINUX-ready or Tru64 UNIX universal country kits include two country-specific power cords, user documentation, and mouse. Tru64 UNIX license is included with system building blocks / CTO models and packaged systems / BTO models.**
- **Windows NT country kits include two country-specific power cords, user documentation, mouse, operating system license, media and documentation.**
- **The following Factory Installed Software (FIS) languages are the only languages delivered.**
  - **English, Japanese, French, Italian, German, Spanish and Dutch**.

Country Supported	Windows NT 4.0 Country Kits	Windows NT 4.0 Media Language	LINUX-ready, OVMS or Tru64 UNIX 4.0F Country Kits	FIS and Documentation Language Supported
Americas				
United States, Canada, Taiwan, Philippines, Thailand, Japan	**SN-PBB0P-AA 388123-001**	English	**SN-PBB0U-AA 388176-001**	English
Canada	**SN-PBB0P-AC 388123-121**	French	**SN-PBB0U-AC 388176-121**	French
Europe				
Denmark	**SN-PBB0P-AD 388123-081**	Danish	**SN-PBB0U-AD 388176-081**	English
Finland	**SN-PBB0P-AF 388123-351**	Finish	**SN-PBB0U-AF 388176-351**	English
Norway	**SN-PBB0P-AN 388123-091**	Norwegian	**SN-PBB0U-AN 388176-091**	English
Sweden	**SN-PBB0P-AM 388123-101**	Swedish	**SN-PBB0U-AM 388176-101**	English
Germany	**SN-PBB0P-AG 388123-041**	German	**SN-PBB0U-AG 388176-041**	German
Netherlands	**SN-PBB0P-AH 388123-331**	Dutch	**SN-PBB0U-AH 388176-331**	Dutch
Italy	**SN-PBB0P-AI 388123-061**	Italian	**SN-PBB0U-AI 388176-061**	Italian
Switzerland/French	**SN-PBB0P-AK 388123-301**	French	**SN-PBB0U-AK 388176-301**	French
Switzerland/Germany	**SN-PBB0P-AL 388123-311**	German	**SN-PBB0U-AL 388176-311**	German
Switzerland/Italian	**SN-PBB0P-AW 388123-321**	Italian	**SN-PBB0U-AW 388176-321**	Italian

Step 7—Country Kits (continued)

Country Supported	Windows NT 4.0 Country Kits		Windows NT 4.0 Media Language	LINUX-ready, OVMS or Tru64 UNIX 4.0F Country Kits		FIS and Documentation Language Supported
Europe *(continued)*						
Switzerland/English	**SN-PBB0P-CH**	**388123-111**	English	**SN-PBB0U-CH**	**388176-111**	English
France, Belgium	**SN-PBB0P-AP**	**388123-051**	French	**SN-PBB0U-AP**	**388176-051**	French
Spain	**SN-PBB0P-AS**	**388123-071**	Spanish	**SN-PBB0U-AS**	**388176-071**	Spanish
United Kingdom	**SN-PBB0P-AE**	**388123-031**	English	**SN-PBB0U-AE**	**388176-031**	English
General European	**SN-PBB0P-EC**	**388123-021**	English	**SN-PBB0U-EC**	**388176-021**	English
Asia Pacific						
Japan	**SN-PBB0P-AJ**	**388123-291**	Japanese	**SN-PBB0U-AJ**	**388176-291**	Japanese
Japan	**SN-PBB0P-CC**	**388123-391**	English	**SN-PBB0U-CC**	**388176-391**	English
Chinese/General Asia	**SN-PBB0P-CA**	**388123-371**	English	**SN-PBB0U-CA**	**388176-371**	English
Chinese	**SN-PBB0P-CV**	**388123-AA1**	Simplified Chinese	**SN-PBB0U-CV**	**388176-AA1**	Simplified Chinese
Australia/New Zealand	**SN-PBB0P-CN**	**388123-011**	English	**SN-PBB0U-CN**	**388176-011**	English

Step 8—Keyboards

- **System building blocks and packaged systems do not include a country specific keyboard. Selection of a keyboard is not mandatory but is essential for full system operation.**
- **Keyboards listed below are colored to match CPU and monitor. Keyboards purchased through distribution channels may not be the correct color match.**

Windows NT Keyboard		LINUX-ready, OVMS or Tru64 UNIX Keyboard		Country
Americas				
SN-LKQ97-AA	**166515-006**	**SN-LKQ47-AA**	**296435-006**	US/English
SN-LKQ97-AC	**166515-126**	**SN-LKQ47-AC**	**296435-126**	Canada/French
SN-LKQ97-AR	**166515-166**	**SN-LKQ47-AR**	**296435-166**	Latin-American/Spanish
SN-LKQ97-AU	**---**	**—**		Brazil
Europe				
SN-LKQ97-AB	**166515-186**	**SN-LKQ47-AB**	**296435-186**	Belgian
SN-LKQ97-AD	**166515-086**	**SN-LKQ47-AD**	**296435-086**	Danish
SN-LKQ97-AE	**166515-036**	**SN-LKQ47-AE**	**296435-036**	UK
SN-LKQ97-AF	**166515-356**	**SN-LKQ47-AF**	**296435-356**	Finland
SN-LKQ97-AG	**166515-046**	**SN-LKQ47-AG**	**296435-046**	German
SN-LKQ97-AH	**166515-336**	**SN-LKQ47-AH**	**296435-336**	Netherlands
SN-LKQ97-AI	**166515-066**	**SN-LKQ47-AI**	**296435-066**	Italy
SN-LKQ97-AK	**166515-116**	**SN-LKQ47-AK**	**296435-116**	Switzerland
SN-LKQ97-AM	**166515-106**	**SN-LKQ47-AM**	**296435-106**	Sweden
SN-LKQ97-AN	**166515-096**	**SN-LKQ47-AN**	**296435-096**	Norway
SN-LKQ97-AP	**166515-056**	**SN-LKQ47-AP**	**296435-056**	France
SN-LKQ97-AS	**166515-076**	**SN-LKQ47-AS**	**296435-076**	Spain
SN-LKQ97-AT	**----**	**SN-LKQ47-AT**	**-----**	Hebrew
SN-LKQ97-AV	**166515-136**	**SN-LKQ47-AV**	**296435-136**	Portugal
SN-LKQ97-AX	**166515-B46**	**SN-LKQ47-AX**	**296435-B46**	Bosnia, Herzagovnia, Croatia, Serbia, Yugoslavia
SN-LKQ97-BH	**166515-156**	**SN-LKQ47-BH**	**296435-156**	Greece

Step 8—Keyboards*(continued)*

Windows NT Keyboard		LINUX-ready, OVMS or Tru64 UNIX Keyboard		Country
Europe *(continued)*				
SN-LKQ97-BP	**166515-246**	**SN-LKQ47-BP**	**296435-246**	Poland
SN-LKQ97-BQ	**166515-216**	**SN-LKQ47-BQ**	**296435-216**	Hungary
SN-LKQ97-BR	**166515-176**	**SN-LKQ47-BR**	**296435-176**	Arabic
SN-LKQ97-BT	**166515-256**	**SN-LKQ47-BT**	**296435-256**	Russia/Cyrillic
SN-LKQ97-BU	**166515-146**	**SN-LKQ47-BU**	**296435-146**	Turkey
SN-LKQ97-BV	**166515-226**	**SN-LKQ47-BV**	**296435-226**	Czech Republic
SN-LKQ97-CZ	**166515-236**	**SN-LKQ47-CZ**	**296435-236**	Slovak
Asia Pacific				
SN-LKQ97-AJ	**166515-296**	**—**	**----**	Japan
SN-LKQ97-BI	**166515-AB6**	**SN-LKQ47-BI**	**296435-AB6**	Taiwan
SN-LKQ97-CV	**-----**	**SN-LKQ47-CV**	**-----**	China
SN-LKQ97-BK	**166515-AD6**	**SN-LKQ47-BK**	**296435-AD6**	South Korean
SN-LKQ97-CB	**166515-286**	**SN-LKQ47-CB**	**296435-286**	Thailand
SN-LKQ97-BA	**166515-B36**	**SN-LKQ47-BA**	**296435-B36**	International

Step 8—Network Options

Systems include an onboard 10/100 Ethernet (Twisted pair)

Part number		Maximum supported per system	Windows NT	Tru64 UNIX or OVMS
SN-PCXAN-DF	**388277-B21**	PCI-based 10Base2 Ethernet (ThinWire) adapter	1	1
SN-PCXAN-DE	**104865-B21**	PCI-based 10Base5 Ethernet (Thick wire) adapter	1	1
SN-DE500-FA	**104877-B21**	PCI-based 10/100 mb/s Fast Ethernet, supports fiber MMF (Multi-Mode Fiber)	2	2
SN-DE500-BA	**104878-B21**	PCI-based 10/100 mb/s Fast Ethernet, supports Twisted pair	2	2
SN-DGLPA-FA	**104891-B21**	PCI-based ATM 155mbps (fiber)- MMF (Multi-Mode Fiber)	—	2
SN-DGLPA-UA	**104892-B21**	PCI-based ATM 155mbps Cat5- UTP	—	2
SN-DEGPA-SA	**104893-B21**	Gigabit Ethernet Adapter	1	1

Step 9—Hardware Supplemental Services

FM-AWXHW-36	3 Year 5x9 Next Business Day Onsite XP900 (must purchase within 90 days of system purchase).
FM-AW4HR-36	3 Year 5x9 Same Day - 4 Hour Response Onsite XP900 (must purchase within 90 days of system purchase).
FM-AW724-36	3 Year 7x24 Same Day - 4 Hour Response Onsite XP900 (must purchase within 90 days of system purchase).
FS-CPQ05-35	Post Warranty XP900 service – 5x9 Next Business Day
FM-IWINS-IN	XP900 Hardware Installation

Step 9a—Software Supplemental Services

For a complete list of available service offerings, please see your local Compaq sales representative or call Compaq directly at 1-800-344-4825 in the US and Canada. For those outside North America, call +353 91 704105 for the number of your local Compaq Information Center.

Tru64 UNIX

FM-3BUNS-12	12 Month 7 x 24 Bronze Software Supplemental Support Services
FM-3BUNS-36	36 Month 7 x 24 Bronze Software Supplemental Support Services
FM-3BUNS-60	60 Month 7 x 24 Bronze Software Supplemental Support Services
FM-3BUN5-12	12 Month 5 x 9 Bronze Software Supplemental Support Services

Step 9a—Software Supplemental Services *(continued)*

FM-3BUN5-36	36 Month 5 x 9 Bronze Software Supplemental Support Services
FM-3BUN5-60	60 Month 5 x 9 Bronze Software Supplemental Support Services

Step 10—Media and Documentation

XP900 User Documentation

EK-?- SI	Compaq Professional Workstation XP900 Installation and Setup Guide—English
EK-?-SI	Compaq Professional Workstation XP900 Installation and Setup Guide—French
EK-?-SI	Compaq Professional Workstation XP900 Installation and Setup Guide—German
EK-?-SI	Compaq Professional Workstation XP900 Installation and Setup Guide—Japanese
EK-?-SI	Compaq Professional Workstation XP900 Installation and Setup Guide—Spanish
EK-?-SI	Compaq Professional Workstation XP900 Installation and Setup Guide—Italian
EK-?-TI	Compaq Professional Workstation XP900 Technical Information Guide – English only

Tru64 UNIX User Documentation, Media and Optional Licenses

For a complete list of available layered Tru64 UNIX software products see the *Software Price List for Digital Products and Services* document available from your local Compaq sales representative or call Compaq at 1-800-344-4825 in the US and Canada. For those outside North America, call +353 91 704105 for the number of your local Compaq Information Center.

QA-MT4AA-H8	Tru64 UNIX Media & Documentation kit
QA-MT4AA-GZ	Tru64 UNIX Full Documentation kit
QA-MT4AB-GZ	Tru64 UNIX End-User Documentation kit
QL-MT7AE-AA	Tru64 UNIX Unlimited User License

Specifications

Height	13 cm (5 inches)
Width	43 cm (17 inches)
Depth	46 cm (18 inches)
Weight	16.3 kg (36 lbs)

Compaq AlphaStation XP900 System Diagrams

FRONT

1. PCI riser card
2. CPU
3. Power supply
4. Space for optional disk
5. CD-ROM
6. System disk
7. Optional bays (2)
8. Control panel
9. Floppy diskette drive
10. Memory

REAR